

1 1. (withdrawn) A torque-transmitting assembly comprising:

2 a) a female coupling member with a bore;

3 b) a radially flexible member, received within the bore, defining a hollow shape
4 with an opening; and

5 c) an elongated shaft member made of a super-elastic alloy, received within the
6 opening,

7 whereupon relative motion among at least two of the members causes the
8 radially flexible member to contact the shaft, inducing a super-elastic activation in
9 the shaft that urges the shaft and radially flexible member into surface-to-surface
10 contact, securing the members together in a fixed relative position.

1 2. (withdrawn) The assembly of Claim 1 wherein the radially flexible member has
2 an external surface that frictionally engages the bore upon relative motion.

1 3. (withdrawn) The assembly of Claim 1 wherein the shaft is tubular with a
2 cannulation.

1 4. (withdrawn) The assembly of Claim 3 wherein the bore of the female coupling
2 member further comprises a cannulation aligned with the shaft cannulation, for
3 common passage of a guide wire there through.

1 5. (withdrawn) The assembly of Claim 1 further comprising an inter-positional
2 polymer sleeve for transmitting bending stress in the assembly.

- 1 6. (withdrawn) The assembly of Claim 1 wherein the contact occurs in one or
2 more areas that frictionally carries the applied torque.
- 1 7. (withdrawn) The assembly of Claim 6 wherein the contact area is calibrated so
2 that the contact slips at a preset torque before the failure strength of the shaft is
3 reached.
- 1 8. (withdrawn) The assembly of Claim 1 wherein the female coupling member
2 further comprises a counter-bore and the radially flexible member has an exterior
3 surface adapted for engagement within the counter-bore.
- 1 9. (withdrawn) The assembly of Claim 8 wherein the radially flexible member is
2 compressed within the counter-bore.
- 1 10. (withdrawn) The assembly of Claim 1 wherein the female coupling member is
2 a fitting that connects the assembly to a cutting tool-bit or powered instrument.
- 1 11. (withdrawn) The assembly of Claim 1 wherein the female coupling member
2 further comprises a fitting with a cutting tool-bit.
- 1 12. (withdrawn) The assembly of Claim 11 wherein the assembly is further
2 connected to a powered instrument.
- 1 13. (withdrawn) The assembly of Claim 1 wherein the radially flexible member is
2 a split collet.
- 1 14. (withdrawn) The assembly of Claim 1, the radially flexible member being in
2 the form of a collar and made of super-elastic alloy, wherein the relative motion
3 further induces a super-elastic activation of the collar.

- 1 15. (withdrawn) The assembly of Claim 1 wherein the collar further comprises a
2 washer.
- 1 16. (withdrawn) The assembly of Claim 15 wherein the collar further comprises a
2 series of washers.
- 1 17. (withdrawn) The assembly of Claim 14 wherein the super-elastic alloy is a
2 nickel-titanium alloy.
- 1 18. (currently amended) A torque-transmitting coupling assembly comprising:
2 a) a split collet member having an exterior surface and an opening;
3 b) an elongated shaft member ~~having solid walls and~~ made of an alloy selected
4 from a group of alloys consisting of super-elastic, bi-metal alloys and super-
5 elastic, tri-metal alloys, including super-elastic, bi-metal and tri-metal nickel-
6 titanium alloys, received within the opening; and
7 c) a sleeve member having an aperture that receives the exterior surface of the
8 collet,
9 whereupon relative motion among at least two of the members causes the opening
10 to contact the shaft, the shaft and the collet being urged into surface-to-surface
11 contact sufficiently to induce a martensitic activation of the super-elastic alloy,
12 thus securing the members together in a fixed relative position.
- 1 19. (previously presented) The assembly of Claim 18 wherein interfering
2 engagement of the exterior surface with the an aperture compresses the opening
3 against the shaft, inducing the martensitic activation in the shaft.

- 1 **20. (original)** The assembly of Claim 18 wherein the shaft is tubular with a
2 cannulation.
- 1 **21. (original)** The assembly of Claim 20 wherein either the sleeve or collet has a
2 cannulation aligned with the shaft cannulation, for common passage of a guide
3 wire there through.
- 1 **22. (original)** The assembly of Claim 18 further comprising an inter-positional
2 polymer sleeve for transmitting bending stress in the assembly.
- 1 **23. (previously presented)** The assembly of Claim 18 wherein surface-to-surface
2 engagement occurs along one or more contact areas that frictionally carries the
3 applied torque.
- 1 **24. (original)** The assembly of Claim 23 wherein the contact area is calibrated to
2 slip at a preset torque before the failure strength of the shaft is reached.
- 1 **25. (previously presented)** The assembly of Claim 18 wherein the collet is
2 adapted for connection to a cutting tool fitting or powered instrument.
- 1 **26. (previously presented)** The assembly of Claim 18 wherein the collet further
2 comprises a cutting tool fitting.
- 1 **27. (previously presented)** The assembly of Claim 26 further adapted for coupling
2 to a powered instrument.
- 1 **28. (withdrawn)** A torque-transmitting coupling assembly comprising:
2 a) a fitting member formed with a counter-bore;

3 b) a collar member made of super-elastic alloy, having an exterior surface and an
4 opening, the collar being located in the counter-bore; and

5 c) an elongated shaft member made of a super-elastic alloy, received within the
6 opening;

7 whereupon relative motion between the fitting and the collar causes the
8 collar to contact the shaft, inducing a super-elastic activation in the shaft that
9 engages the shaft and collar into surface-to-surface contact, securing the members
10 together in a fixed relative position.

1 29. (withdrawn) The assembly of Claim 28 wherein engagement of the exterior
2 surface with the counter-bore super-elastically compresses the opening against the
3 shaft.

1 30. (withdrawn) The assembly of Claim 29 wherein the collar further comprises a
2 washer.

1 31. (withdrawn) The assembly of Claim 30 further comprising a series of washers.

1 32. (withdrawn) The assembly of Claim 28 wherein the super-elastic alloy is a
2 nickel-titanium alloy.

1 33. (withdrawn) The assembly of Claim 28 wherein the shaft is tubular with a
2 cannulation.

1 34. (withdrawn) The assembly of Claim 33 wherein the fitting has a cannulation
2 aligned with the shaft cannulation, for common passage of a guide wire there
3 through.

- 1 35. (withdrawn) The assembly of Claim 28 further comprising an inter-positional
2 polymer sleeve for transmitting bending stress in the assembly.
- 1 36. (withdrawn) The assembly of Claim 29 wherein the frictional engagement
2 occurs along one or more contact areas that frictionally carries the applied torque.
- 1 37. (withdrawn) The assembly of Claim 36 wherein the contact area is calibrated
2 so that the coupling slips at a preset torque before the fatigue strength of the shaft
3 is reached.
- 1 38. (withdrawn) The assembly of Claim 28 wherein the fitting is connected to a
2 cutting tool-bit or powered instrument.
- 1 39. (withdrawn) The assembly of Claim 28 wherein the fitting further comprises a
2 cutting tool-bit.
- 1 40. (withdrawn) The assembly of Claim 39 further coupled to a powered
2 instrument.
- 1 41. (withdrawn) A method of forming a torque-transmitting assembly, comprising
2 the steps of:
- 3 a) providing a female coupling member with a bore;
- 4 b) providing a radially flexible member with an external surface and an opening,
5 situating the radially flexible member within the bore
- 6 c) providing an elongated shaft member made of a super-elastic alloy, received
7 within the opening; and

8 d) relatively moving at least two of the members, causing the radially flexible
9 member to contact the shaft, inducing a super-elastic activation in the shaft that
10 urges the shaft and radially flexible member into surface-to-surface contact,
11 securing the members together in a fixed relative position.

1 42. (withdrawn) The method of Claim 41 wherein step d) further comprises
2 frictionally engaging the members along a contact area that carries the applied
3 torque, the contact area being calibrated to slip at a preset torque before the failure
4 strength of the shaft is reached.

1 43. (withdrawn) The method of Claim 42 further comprising the steps of
2 providing the female coupling member with a counter-bore, providing the radially
3 flexible member in the form of a collar made of super-elastic alloy and inducing a
4 super-elastic activation in the collar.

1 44. (withdrawn) The method of Claim 42 wherein step a) further comprises providing a
2 radially flexible member in the form of a split collet.

1 45. (withdrawn) A flexible surgical reamer having a torque-transmitting assembly
2 and comprising:

3 a) a fitting member formed with a counter-bore and including a cutting tool-bit;

4 b) a collar member made of super-elastic alloy, located in the counter-bore; and

5 c) an elongated shaft member made of a super-elastic alloy, adapted for receipt
6 within the collar;

7 whereupon relative motion among the members causes the opening to
8 contact the shaft, inducing a super-elastic activation in the shaft that urges the
9 shaft and the collar into surface-to-surface contact, securing the members together
10 in a fixed relative position.

1 46. (withdrawn) The reamer of Claim 45 wherein the collar is an annular member.

1 47. (withdrawn) The reamer of Claim 46 wherein the collar further comprises a
2 washer.

1 48. (withdrawn) The reamer of Claim 47 wherein the collar further comprises a
2 series of washers.

1 49. (withdrawn) The reamer of Claim 48 wherein the collar is pre-assembled with
2 the fitting.

1 50. (withdrawn) The reamer of Claim 45 further comprising an inter-positional
2 polymer sleeve for transmitting bending stress in the assembly.

1 51. (withdrawn) The reamer of Claim 45 wherein the contact occurs along an area
2 that frictionally carries the applied torque.

1 52. (withdrawn) The reamer of Claim 51 wherein the contact area is calibrated to slip at
2 a preset torque before the failure strength of the shaft is reached.

1 53. (withdrawn) The reamer of Claim 45 wherein the shaft is tubular, with a
2 cannulation.

1 54. (withdrawn) The reamer of Claim 53 wherein the fitting has a cannulation that
2 aligns with the shaft cannulation for passage of a guide wire through the reamer.

1 55. (withdrawn) A flexible surgical reamer having a torque-transmitting assembly
2 and comprising:
3 a) a radially flexible member having a split collet with an exterior surface and an
4 opening, and including a cutting tool-bit;
5 b) an elongated shaft member made of a super-elastic alloy, received within the
6 opening; and
7 c) a sleeve having a bore that receives the exterior surface,
8 whereupon relative motion among the members causes the opening to contact the
9 shaft, inducing a super-elastic activation in the shaft that urges the shaft and the
10 collet into surface-to-surface contact, securing the members together in a fixed
11 relative position.

1 56. (withdrawn) The reamer of Claim 55 wherein the exterior surface is
2 compressed by the bore, further contracting the opening against the shaft to induce
3 the super-elastic activation.

1 57. (withdrawn) The reamer of Claim 55 wherein the shaft is tubular with a
2 cannulation for passage of a guide wire there through.

1 58. (withdrawn) The reamer of Claim 56 wherein the opening interferingly
2 receives the shaft and is expanded to compress the exterior surface against the
3 bore.

- 1 59. (withdrawn) The reamer of Claim 55 further comprising an inter-positional
2 polymer sleeve for transmitting bending stress in the assembly.
- 1 60. (withdrawn) The reamer of Claim 55 wherein the contact occurs along an area
2 that frictionally carries the applied torque.
- 1 61. (withdrawn) The reamer of Claim 60 wherein the contact area is calibrated to
2 slip at a preset torque before the failure strength of the shaft is reached.
- 1 62. (withdrawn) The reamer of Claim 61 wherein the shaft is further connected to
2 a powered instrument.